## **TestHorse**

Certified IT practice exam authority

Accurate study guides, High passing rate! Testhorse provides update free of charge in one year!

**Exam** : HP0-662

Title : NonStop Configuration and

**Planning** 

Version: DEMO

| 1. Assuming no I/O enclosures, how many electrical branch circuits are needed to provide power fault   |
|--|
| tolerance for a six-processor S7x000 system?   |
| A. 2   |
| B. 3   |
| C. 4   |
| D. 6   |
| Answer: D  |
|  |
| 2. Which items would you expect to see on a network topology diagram? Select TWO.                      |
| A. tape devices  |
| B. IP addresses  |
| C. routers   |
| D. disk mapping  |
| E. cable specifications  |
| Answer: BC   |
|  |
| 3. What allows a customer to track open problem cases through the Web?                                 |
| A. Scout for NonStop servers   |
| B. Express Notice  |
| C. NonStop Technical Library (NTL)   |
| D. Total Web Support (TWS)   |
| Answer: D  |
|  |
| 4. Which prediction is NOT produced by TCM?  |
| A. number of processors required   |
| B. number of logical disk volumes  |
| C. network response time   |
| D. processor and disk utilization  |
| Answer: C  |
| 5. Which tool simplifies the task of migrating a database from many small disks to a smaller number of |

| large disks?   |
|--|
| A. MEDIACOM  |
| B. ASAP  |
| C. SMF   |
| D. MAPPER  |
| Answer: C  |
|  |
| 6. DSM/SCM can be used to control customer software. Which program is used to prepare the  |
| software?  |
| A. CNFGINFO  |
| B. ZPHIRNM   |
| C. INITENV   |
| D. INITSTAT  |
| Answer: A  |
|  |
| 7. To what type of adapter does a default configuration system console connect?            |
| A. E4SA  |
| B. MIOE  |
| C. FESA  |
| D. TRSA  |
| Answer: B  |
|  |
| 8. Which process needs to be configured to ensure Expand connectivity between two systems? |
| A. \$znet  |
| B. \$ncp   |
| C. \$expand  |
| D. \$zzatm   |
| Answer: B  |
|  |
| 9. How many internal disk SCSI controllers are on a PMF CRU?                               |

| A. 0   |
|--|
| B. 1   |
| C. 2   |
| D. 3   |
| Answer: C  |
|  |
| 10. Which element is typically included in a separate document in response to a Request for Proposal |
| (RFP)?   |
| A. software details  |
| B. timescales  |
| C. cost breakdown  |
| D. hardware details  |
| Answer: C  |
|  |
| 11. Increasing the number of processors in a system  |
| A. provides fault tolerance for the system consoles  |
| B. allows more disk units in group 1 of the system   |
| C. requires a cold load of the system  |
| D. allows more low-pin processes to run in the system  |
| Answer: D  |
|  |
| 12. Which product can be used to project transaction growths into a resource upgrade timeline?       |
| A. GPA   |
| B. ASAP  |
| C. NSX   |
| D. TCM   |
| Answer: D  |
|  |
| 13. What is the filename of the SCSI boot code for the G06.08 release?                               |
| A. I1000   |

| B. IBOOT  |
|---|
| C. 12000  |
| D. ISCSI  |
| Answer: B   |
|   |
| 14. Which utility is used for routine tape management operations?                   |
| A. TAPECOM  |
| B. NSKCOM   |
| C. MEDIACOM   |
| D. TMFCOM   |
| Answer: C   |
|   |
| 15. Which product requires a manual firmware update using TSM?                      |
| A. FESA   |
| B. E4SA   |
| C. SWAN   |
| D. TRSA   |
| Answer: C   |
|   |
| 16. Which tool has replaced Timbuktu for remote support?                            |
| A. Timbuk3  |
| B. Remote Copy  |
| C. Carbon Copy  |
| D. PC Anywhere  |
| Answer: C   |
|   |
| 17. What is a key difference between TSM low-level link and TSM service connection? |
| A. service connection communicates only with the MSP                                |
| B. service connection shows external devices  |
| C. service connection allows firmware updates                                       |

| Answer: B  |
|--|
|  |
| 18. Which Windows NT services are required when configuring dial-out on TSM? Select TWO. |
| A. RPC   |
| B. RAS   |
| C. SAP Agent   |
| D. Network Monitor Agent   |
| E. SNMP  |
| Answer: BE   |
|  |
| 19. In which volume and subvolume do the hardware configuration files reside?            |
| A. \$system.system   |
| B. \$system.sysnn  |
| C. \$system.zsysconf   |
| D. \$dsmscm.system   |
| Answer: C  |
|  |
| 20. How can the ServerNet connectivity to CPU 5 be displayed in SCF?                     |
| A. INFO SERVERNET 5  |
| B. STATUS SERVERNET \$ZSNET  |
| C. INFO SERVERNET \$ZSNET  |
| D. STATUS SERVERNET 5  |
| Answer: B  |
|  |
|  |

D. service connection allows system discovery