TestHorse

Certified IT practice exam authority

Accurate study guides, High passing rate!
Testhorse provides update free of charge in one year!

http://www.testhorse.com

Exam : **MA0-101**

Title : McAfee Certified Product Specialist – NSP

Version : Demo

1.Which port needs to be opened for Alert Channel communication between Sensor and Manager through a firewall?
A. 8501
B. 8502
C. 8503
D. 8555
Answer: B

2.Setting a threshold to allow an IPS to react when traffic volume exceeds the set limit is an example of what type of detection method.?
A. Signature based
B. Pattern matching
C. Denial of Service
D. Remediation
Answer: C

3.Performance debugging mode can be enabled on a sensor for a specified time duration by issuing which of the following CLI commands?
A. sensor perf-debug 100
B. sensor perf-debug on 100
C. sensor perf-debug Interface all 100
D. sensor perf-debug assert 100
Answer: A

4.What type of encryption is used for file transfers between the Sensor and the Manager?
A. SSL with RC4
B. SSL with MD5
C. SSL with RC4 and MD5
D. DES
Answer: D

5.When placed in Layer3 mode, a Sensor detects a Layer2 device based on which of the following?
A. MAC address
B. IP address
C. DNS
D. Subnet
Answer: B

6.What is the CLI command that enables the output of the MAC/IP address mapping table to the sensor debug files?
A. arp spoof status
B. arp spoof enable
C. arp dump
D. arp flush

Answer: C

7.DoS detection is implemented in which of the following modes? (Choose two)
A. Learning mode
B. Configuration mode
C. Threshold mode
D. Bidirectional mode
E. Inbound mode
Answer: A,C

8.Which port needs to be opened for Packet Log Channel communication between Sensor and Manager through a firewall?
A. 8501
B. 8502
C. 8503
D. 8555
Answer: C

9.Which port is correctly defined for the Alert Channel on the Network Security Manager?
A. 8500
B. 8501
C. 8502
D. 8504
Answer: C

10.In double VLAN tagging, a second VLAN tag that is inserted into the frame is referred to as which of the following?
A. Customer Identification tag (CD)
B. VLAN Identification tag (VID)
C. Outer Identification tag (OID)
D. Inner Identification tag (HD)
Answer: A

11.Which of the following information is unique to Host Intrusion Prevention alerts? (Choose three)
A. Destination IP
B. User
C. Source IP
D. Agent IP
E. Agent name
Answer: B,D,E

12.Which mode is used when certain hosts are located on the same network as a sensor and other hosts enter through a router or VPN?
A. Mixed

B. Hybrid
C. Enforcement
D. Prevention
Answer: A

13.Which mode needs to be set to redirect an unmanaged system to the guest portal?
A. Audit
B. Simulation
C. Enforcement
D. Prevention
Answer: C

14.Which attack cannot be blocked when the sensor has been set for in-line mode?
A. TCP Control Anomaly
B. ICMP Echo Anomaly
C. Too Many Inbound Syn
D. SCADA Attacks
Answer: A

15.Which database is supported for Network Security Manager?
A. MSSQL
B. Oracle
C. MySQL
D. Sybase
Answer: C